

Socket Scanner CHS 7Ci - Android

Copyright 2016 Novex Software Development, Inc. All rights reserved.

1 Unpair the scanner

1. Ensure the scanner is powered on.
2. Hold the *power* and *scan* buttons simultaneously.
3. You will hear three falling tones when the scanner unpairs.

2 Unpair the Android device

1. Open the *Settings* app, and find the *Bluetooth* options.
2. Find the **Socket CHS** entry (may be under *Paired Devices*).
3. Choose to forget the Socket CHS pairing.

3 Factory reset the scanner

1. Ensure the scanner is unpaired and powered on.
2. Scan the following code to reset all configuration on the scanner:



3. You will hear a musical chime, and the scanner will power off.

4 Configure the scanner for SPP Mode

1. Ensure the scanner is unpaired and powered on.
2. Scan the following code to enable SPP mode. You will hear three rising tones.



5 Pair the scanner to an Android device

1. Ensure the scanner is unpaired and powered on.
2. Open the *Settings* app, and find the *Bluetooth* options.
3. Find the **Socket CHS** entry (may be under *Available Devices*).
4. Choose to pair, and wait for the scanner to connect.
5. Open *ZiiZii*, and choose *Settings* from the main screen. Select *Socket Mobile SPP scanners* as the Bluetooth scanner module.
6. The scanner should beep within 5 seconds, and connect shortly after. A message will appear on screen indicating you have connected.

6 Android scanning help

1. Remember that all scanners must be unpaired, both on the scanner itself, and the device.
2. Android devices require all scanners to be in SPP mode **before** pairing with the device.

Socket Scanner CHS 7Ci - Android



Enable MSI
(01h)



Transmit MSI Check Digit (Enable)
(01h)